



Adjustment range is the maximum range of adjustment. Cable lengths will be calculated with 1/3rd engagement allowing 2/3rd for shortening the length. E.g. C2-5mm would have approximate adjustment range of +32mm - 64mm.



PRODUCT CODE	W Dia	CBL(KN) MBL *9	MBL	PIN	TH Dia.	C	T	FORK LENGTH	ADJUSTMENT RANGE
C2-3mm	3mm	6.678	7.42	6.4mm	6.3mm	15mm	7mm	55	48mm
C2-4mm	4mm	11.88	13.2	8mm	7.9mm	16mm	7.9mm	70	64mm
C2-5mm	5mm	18.54	20.6	9.5mm	9.1mm	19mm	9.5mm	88	80mm
C2-6DS	6mm	26.73	29.7	9.5mm	9.1mm	19mm	9.5mm	88	80mm
C2-6mm	6mm	26.73	29.7	11mm	12.5mm	22mm	10.9mm	98	88mm
C2-7mm	7mm	34.02	37.8	13mm	14.3mm	30mm	12.7mm	120	96mm
C2-8DS	8mm	44.46	49.4	13mm	16.0mm	30mm	12.7mm	120	96mm
C2-8mm	8mm	44.46	49.4	16mm	16.0mm	32mm	15.8mm	142	128mm
C2-10mm	10mm	69.48	77.2	16mm	18.0mm	32mm	15.8mm	142	128mm
C2-12mm	12mm	93.6	104	19mm	21.4mm	38mm	19mm	160	142mm
C2-14mm	14mm	125.1	139	22.2mm	25.0mm	45mm	22.2mm	179	160mm
C2-16mm	16mm	162.9	181	25.4mm	28.2mm	50mm	25mm	207	180mm
C2-19mm	19mm	209.7	233	28.4mm	34.5mm	58mm	28.4mm	231	200m
C2-22mm	22mm	269.1	299	32mm	40.3mm	64mm	32mm	252	220mm
C2-26mm	26mm	374.4	416	35mm	45.9mm	70mm	34.9mm	278	240mm

P = Pin diameter. C = Fork depth from pin centre. T = Throat width