



Adjustment range is the maximum range of adjustment. Cable lengths will be calculated with 1/3rd engagement allowing 2/3rd for shortening the length. E.g. C4-5mm would have approximate adjustment range of +33mm - 66mm.



PRODUCT CODE	W Dia	CBL(KN) MBL *9	MBL	PIN	TH Dia.	C	T	MIN L	MAX L
C4-3mm	3mm	6.678	7.42	6mm	6.3mm	12.5mm	6.2mm	125mm	195mm
C4-4mm	4mm	11.88	13.2	8mm	7.9mm	17mm	7.9mm	150mm	228mm
C4-5DS	5mm	18.54	20.6	8mm	7.9mm	17mm	7.9mm	15300	231mm
C4-5mm	5mm	18.54	20.6	9.5mm	9.1mm	19mm	9.9mm	184mm	284mm
C4-6DS	6mm	26.73	29.7	9.5mm	9.1mm	19mm	9.9mm	187mm	287mm
C4-6mm	6mm	26.73	29.7	11mm	12.5mm	22mm	10.9mm	202mm	310mm
C4-7mm	7mm	34.02	37.8	12mm	14.3mm	25mm	12.7mm	236mm	368mm
C8-8DS	8mm	44.46	49.4	12mm	16.0mm	25mm	12.7mm	239mm	371mm
C8-8mm	8mm	44.46	49.4	14mm	16.0mm	28mm	15.8mm	300mm	455mm
C4-10mm	10mm	69.48	77.2	16mm	18.0mm	32mm	15.8mm	312mm	468mm
C4-12mm	12mm	93.6	104	19mm	21.4mm	38mm	17.8mm	361mm	532mm
c4-14mm	14mm	125.1	139	22mm	25.0mm	45mm	22mm	403mm	600mm
C4-16mm	16mm	162.9	181	25.4mm	28.2mm	50mm	25mm	472mm	711mm
C4-19mm	19mm	209.7	233	28mm	34.5mm	58mm	28.5mm	531mm	801mm
C4-22mm	22mm	269.1	299	32mm	40.3mm	64mm	31.8mm	575mm	859mm
C4-26mm	26mm	374.4	416	35mm	45.9mm	70mm	34.9mm	655mm	979mm

P = Pin diameter. C = Fork depth from pin centre. T = Throat width

