



Adjustment range is the maximum range of adjustment. Cable lengths will be calculated with 1/3rd engagement allowing 2/3rd for shortening the length. E.g. C5-5mm would have approximate adjustment range of +33mm - 66mm.



PRODUCT CODE	W Dia	CBL(KN) MBL *9	MBL	W	P	C	T	ADJUSTMENT RANGE
C5-3mm	3mm	6.678	7.42	3mm	6.0mm	14mm	8mm	70mm
C5-4mm	4mm	11.88	13.2	4mm	8mm	18mm	9mm	78mm
C5-5mm	5mm	18.54	20.6	5mm	9.5mm	21mm	11mm	78mm
C5-6mm	6mm	26.73	29.7	6mm	11mm	25mm	13mm	100mm
C5-7mm	7mm	34.02	37.8	7mm	12mm	27mm	15mm	132mm
C5-8DS	8mm	44.46	49.4	8mm	12mm	27mm	15mm	132mm
C5-8mm	8mm	44.46	49.4	8mm	12mm	27mm	15mm	155mm
C5-10mm	10mm	69.48	77.2	10mm	16mm	36mm	19mm	156mm
C5-12mm	12mm	93.6	104	12mm	19mm	45mm	22mm	171mm
C5-14mm	14mm	125.1	139	14mm	22mm	53mm	25mm	197mm
C5-16mm	16mm	162.9	181	16mm	25.4mm	62mm	28mm	239mm
C5-19mm	19mm	209.7	233	19mm	28mm	63mm	32mm	270mm
C5-22mm	22mm	269.1	299	22mm	32mm	76mm	35mm	284mm
C5-26mm	26mm	374.4	416	26mm	35mm	92mm	38mm	324mm

P = Pin diameter. C = Fork depth from pin centre. T = Throat width

