



Fixed length tendon. Suitable for applications where the cable is tensioning by either movement in the supporting structure or from supporting a vertical load. Please note cable fabrication tolerance of +/- 3mm



PRODUCT CODE	W Dia	CBL(KN) MBL *9	MBL	PIN	D	C	T
C6-3mm	3mm	6.678	7.42	6mm	6.3mm	12.5mm	6.2mm
C6-4mm	4mm	11.88	13.2	8mm	7.5mm	17mm	7.9mm
C6-5DS	5mm	18.54	20.6	9.5mm	9.1mm	19mm	9.9mm
C6-5mm	5mm	18.54	20.6	11mm	12.5mm	22mm	10.9mm
C6-DS	6mm	26.73	29.7	11mm	12.5mm	22mm	10.9mm
C6-6mm	6mm	26.73	29.7	11mm	12.5mm	22mm	10.9mm
C6-7mm	7mm	34.02	37.8	12mm	14.3mm	25mm	12.7mm
C6-8DS	8mm	44.46	49.4	12mm	16.0mm	25mm	12.7mm
C6-8mm	8mm	44.46	49.4	14mm	16.0mm	28mm	13.8mm
C6-10mm	10mm	69.48	77.2	16mm	18.0mm	32mm	15.8mm
C6-12mm	12mm	93.6	104	19mm	21.4mm	38mm	17.8mm
C6-14mm	14mm	125.1	139	22mm	25.0mm	45mm	22mm
C6-16mm	16mm	162.9	181	25.4mm	28.2mm	50mm	25mm
C6-19mm	19mm	209.7	233	28mm	34.5mm	58mm	28.2mm
C6-22mm	22mm	269.1	299	32mm	40.3mm	64mm	31.8mm
C6-26mm	26mm	374.4	416	35mm	45.9mm	70mm	34.8mm

P = Pin diameter. C = Fork depth from pin centre. T = Throat width

